

Dialight

COMBINATION HAND and WALKING PERSON PEDESTRIAN SIGNALS



FEATURES / BENEFITS

- ▲ 90% reduction in power vs. incandescent
- ▲ Long life; up to 10 times longer than incandescent
- ▲ Sealed moisture resistant enclosure
- ▲ Lens available to fit most pedestrian heads
- ▲ Lens has a textured surface to reduce glare
- ▲ Wide selection of products
- ▲ Easy to install into existing signal enclosure
- ▲ Most types certified to EPA Energy Star

SPECIFICATIONS

- ▲ Operating Voltage Range: 80VAC to 135VAC (120VAC nominal)
- ▲ Fuse and transient suppressor incorporated for line and load protection
- ▲ Operating Temperature Range: -40°C to +74°C
- ▲ Turn-On/Turn-Off Time = 75 msec max
- ▲ Power factor >0.9
- ▲ Total harmonic distortion <20%
- ▲ Meets FCC Title 47, Subpart B, Section 15 Regulations for electrical noise
- ▲ Provided with quick connect terminals and Spade adapters
- ▲ Written manufacturer's warranty available on request
- ▲ All products traceable by serial number
- ▲ LED Colors:
Hand - Portland Orange
Walking Person - Lunar White

TYPICAL OPERATING CHARACTERISTICS

Part Number	CSA Approved*	EPA Certified	Approved by Caltrans	WATTAGE		SYMBOL		
				Hand	Person	Hand	Person	Housing Size
OVERLAY								
430-6471-001	●	●		9	6	Filled	Outline	16x18
430-6472-001	●	●		8	7	Filled	Filled	16x18
430-6771-001		●		8	7	Filled	Outline	12x12
430-6772-001		●		8	7	Filled	Filled	12x12
430-6774-001	●	●		6	7	Outline	Outline	12x12
SIDE BY SIDE								
430-6473-001	●	●	●	9	7	Filled	Filled	16x18
430-6473-801				8	7	Filled	Filled	16x18
430-6476-001	●	●		6	7	Outline	Outline	16x18

*CSA approval is to Std. 250 for Luminaires

Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA

Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com



a Roxboro Group Company



MDTSPDCX001_E