

Dialight

HI-FLUX INCANDESCENT APPEARANCE LED ARROWS



FEATURES / BENEFITS

- ▲ New Hi-Flux Incandescent Appearance
- ▲ 90% reduction in power vs. incandescent
- ▲ Long life; up to 10 times longer than incandescent
- ▲ Hard coated lenses for abrasion resistance
- ▲ Easy to install into existing signal enclosure

SPECIFICATIONS

- ▲ Operating Voltage Range: 80VAC to 135VAC (120VAC nominal)
- ▲ Convex lens reduces glare & sun reflection
- ▲ Fuse and transient suppressor incorporated for line and load protection
- ▲ Operating Temperature Range: -40°C to +74°C
- ▲ Turn-On/Turn-Off Time = 75 msec max
- ▲ Power factor >0.9
- ▲ Total harmonic distortion <20%
- ▲ Meets FCC Title 47, Subpart B, Section 15 Regulations for electrical noise
- ▲ Conforms to MIL-STD-810F for blowing rain
- ▲ Provided with quick connect terminals and spade adapters
- ▲ Written manufacturer's warranty available on request
- ▲ All products traceable by serial number

12" (300mm) - 120 VOLT ARROWS

Part Number	Description	Lens Type	EPA Certified	Typical Wattage at 25°C	Dominant Wavelength (nm)
435-1314-001	Red, Hi-Flux	Tinted	✓	7	622
435-3334-001	Yellow, Hi-Flux	Tinted		14	590
435-2324-001	Green, Hi-Flux	Tinted		18	505
435-2374-001	Green, Hi-Flux	Clear		18	505
435-6370-001	Bi-Modal Green/Yellow, Hi-Flux	Clear		9/10	505/590



Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA

Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com



a Roxboro Group Company

MDTSARWNHF001_A